

A Temporal Logic For Network Flow Analysis

Tim Shimeall tjs@cert.org

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding an DMB control number.	ion of information. Send comment arters Services, Directorate for Inf	s regarding this burden estimate formation Operations and Reports	or any other aspect of the s, 1215 Jefferson Davis	nis collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE JAN 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
A Temporal Logic For Network Flow Analysis				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Carnegie Mellon University ,Software Engineering Institute,Pittsburgh,PA,15213				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAIL Approved for publ	ABILITY STATEMENT ic release; distributi	on unlimited				
13. SUPPLEMENTARY NO	OTES					
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	12		

Report Documentation Page

Form Approved OMB No. 0704-0188

NO WARRANTY

THIS MATERIAL OF CARNEGIE MELLON UNIVERSITY AND ITS SOFTWARE ENGINEERING INSTITUTE IS FURNISHED ON AN "AS-IS" BASIS. CARNEGIE MELLON UNIVERSITY MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, AS TO ANY MATTER INCLUDING, BUT NOT LIMITED TO, WARRANTY OF FITNESS FOR PURPOSE OR MERCHANTABILITY, EXCLUSIVITY, OR RESULTS OBTAINED FROM USE OF THE MATERIAL. CARNEGIE MELLON UNIVERSITY DOES NOT MAKE ANY WARRANTY OF ANY KIND WITH RESPECT TO FREEDOM FROM PATENT, TRADEMARK, OR COPYRIGHT INFRINGEMENT.

Use of any trademarks in this presentation is not intended in any way to infringe on the rights of the trademark holder.

This Presentation may be reproduced in its entirety, without modification, and freely distributed in written or electronic form without requesting formal permission. Permission is required for any other use. Requests for permission should be directed to the Software Engineering Institute at permission@sei.cmu.edu.

This work was created in the performance of Federal Government Contract Number FA8721-05-C-0003 with Carnegie Mellon University for the operation of the Software Engineering Institute, a federally funded research and development center. The Government of the United States has a royalty-free governmentpurpose license to use, duplicate, or disclose the work, in whole or in part and in any manner, and to have or permit others to do so, for government purposes pursuant to the copyright license under the clause at 252 227-7013

Overview

Motivation

Temporal Logic

Application to Flow

Example

Implementations

Motivation

Clarify timing relationships

Formalize analysis semantics

- Clearer discussions
- Enhance automation & frameworks
- Combining analyses

Avoid over-specification of timing

Support reasoning about analysis tasks

Access temporal logic methods

Temporal Logic

Logic with explicit inclusion of time

Classically, first-order logic, could be any logic form

Temporal interpretation: Instantiating circumstances

- Linear time with rollback on contradiction
- Branching time with branch termination on contradiction
- Advantage to linear: simpler structure, no worry over paths
- Advantage to branching: can express path-related conditions

Temporal Logic Operators

Next(t,p) - p is true in the instant after t

Global(p) - p is true independent of time

Following(t, p) - p is true at some instant after t

Until(t,p,q)-p is true at each instant after t until q is true

Forall (p) – p is true along all paths

Exists (p) – p is true along at least one path



Adaptation to Flow

Description first, then reasoning

Iterative semantics – suitable for filter-like processing

Specific semantics:

- 5-tuple
- Ordinal time (inexact comparisons)
- Related flows

Adapted semantics

 $R(f_1,f_2)$ relation – flow-flow connection

p(f,...), q(f,...) – logic predicates on flow records/fields

Enable reasoning using Horn clause resolution and backtracking

Temporal Operators for Flow

Globally: G(p): forall($R(f,f') \rightarrow p(f)$ and p(f')) Next: N(f,f'): iff R(f,f') and f'.stime > f.stime and does not exists (R(f,f'') and f'.stime > f''.stime > f.stime)N*(f,f'): transitive relation on N X(f,p): forall($N(f,f') \rightarrow p(f')$) Following: F(f,p): exists($N^*(f,f')$ and p(f')) **Until:** U(f,p,q): exists $(N^*(f,f'')$ and q(f''),

forall $(N^*(f,f'))$ and f'' stime>f'.stime $\rightarrow p(f')$ and not q(f')

Descriptive Temporal Example

```
Spam(s,f):
   R(f,f'): f.sip = f'.sip = s and s not on whitelist
   If and only if
      |{f', Following(f,f',f'.stime < f.stime+5min and
       f'.dport=email)}|>15 and
    |{f', Following(f,f', f'.stime < f.stime+5min and
       f'.dport=email)}| ≥
      |\{f', Following(f,f', f'.stime < f.stime + 5min)\}| * 0.1
```

Implementation

Use temporal logic to express analysis criteria Prolog-based (GNU-Prolog)

Logic programming, incorporating time in resolution Initial prototype to refine semantics

Construct interface to analysis tools (plugin)

Python-based (PySiLK)

Declarative programming, incorporate limited resolution mechanism

Secondary prototype to demonstrate applicability

Eventually construct reasoning rules for analysis relationships or proof





Conclusions

Temporal logic adaptation of flow analysis offers opportunity to encompass large literature of preexisting methods

Formalization of time relationships offers opportunity to improve flow analysis methods

More formal reasoning on flow analysis?